MODEL #NEPTH18-454

Euro Pro Wall Mount Hood with High-Capacity Magic Lung® Blower

European styling and clean geometric lines give this hood a refined architectural presence. Higher-capacity Magic Lung® blower configurations deliver enhanced performance for demanding cooking environments, with patented centrifugal filtration for powerful yet exceptionally quiet ventilation. SensaSource® automatically adjusts blower speed for enhanced grease control and fire safety, while dishwasher-safe components simplify cleanup. Matching duct covers sold separately.

To view available finishes & accessories please visit ventahood.com/products/NEPTH18-454

SPECIFICATIONS

WIDTH	54"
DEPTH	24"
HEIGHT	18"
CFM [1]	1200
EQUIVALENT CFM [2]	1800
SOUND RATING (HIGH SPEED) [3]	6.6 Sones / 57.2 dB
LIGHTING [4]	4 LEDs 2700K Warm White



DUCT COVERS



Wall Mount Duct Cover
Models: WDCRND-26/12, WDCRND-26/24, WDCRND-26/36

RECOMMENDED MOUNTING HEIGHT



NOTE: Exceeding recommended mounting height may compromise performance.

CONNECTIONS



1200 CFM Double B200 Dual Blowers (Top View)



VP563 Standard Transition Installed (Front View)



The transition shown (VP563) is installed in the hood at the factory as a standard item. It will be located in the exact center of the duct cover (left to right & front to rear).

ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT

MODEL	VOLTS	AMPS	HZ	RPM	CFM @ 0.0" SP[5]	CFM @ 0.1" SP	CFM @ 0.2" SP	CFM @ 0.3" SP	MIN. ROUND DUCT SIZE
2 × B200 Dual	**115**	**7.5**	**60**	**1550**	**1200**	**1062**	**960**	**860**	**12" (113sq.in.)**

[1] CFM (cubic feet per minute) measures airflow. [2] Because Magic Lung® blowers use centrifugal filtration instead of traditional baffle or mesh filters, they move air more efficiently. When comparing to other brands, use Equivalent CFM to understand real-world performance. [3] Sones measure perceived loudness—lower values indicate quieter operation. Decibel values shown are approximate equivalents. [4] This model is not available with heat lamps. [5] Airflow (CFM) decreases as duct resistance (static pressure) increases. Values at 0.1"–0.3" SP reflect typical installed conditions.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE 062626