MODEL #NPH18-460

Professional Wall Mount Hood with Rounded Edges, Magic Lung® Blower

Softly rounded corners give this professional-style hood a more sculpted architectural look. Patented Magic Lung® technology delivers powerful yet exceptionally quiet ventilation through centrifugal filtration, while SensaSource® automatically adjusts blower speed for enhanced grease control and fire safety. Dishwasher-safe components simplify cleanup. Matching duct covers sold separately.

To view available finishes & accessories please visit ventahood.com/products/NPH18-460

SPECIFICATIONS

WIDTH	**60"**
DEPTH	**24"**
HEIGHT	**18"**
CFM [1]	**1200**
EQUIVALENT CFM [2]	**1800**
SOUND RATING (HIGH SPEED) [3]	**6.6 Sones / 57.2 dB**
LIGHTING [4]	**4 LEDs 2700K Warm White**



DUCT COVERS



Wall Mount Duct Cover
Models: WDCRND-*

RECOMMENDED MOUNTING HEIGHT



NOTE: Exceeding recommended mounting height may compromise performance.

CONNECTIONS



1200 CFM Double B200 Dual Blowers (Top View)



VP563 Transition (Optional) For B400 (Double B200 Dual Blowers)



VP563 transition centers outlet over top of hood.

ELECTRICAL/MECHANICAL SPECIFICATIONS FOR BLOWER UNIT

MODEL	VOLTS	AMPS[5]	HZ	RPM	CFM @ 0.0" SP[6]	CFM @ 0.1" SP	CFM @ 0.2" SP	CFM @ 0.3" SP	MIN. ROUND DUCT SIZE
2 × B200 Dual	**115**	**7.5**	**60**	**1550**	**1200**	**1062**	**960**	**860**	**12" (113sq.in.)**

[1] CFM (cubic feet per minute) measures airflow. [2] Because Magic Lung® blowers use centrifugal filtration instead of traditional baffle or mesh filters, they move air more efficiently. When comparing to other brands, use Equivalent CFM to understand real-world performance. [3] Sones measure perceived loudness—lower values indicate quieter operation. Decibel values shown are approximate equivalents. [4] WBAR warming light bar is available on selected models. [5] Add 2.5 amps for each warming light. This model is equipped with LED lighting: (2 lights: 30" - 41", 3 lights: 42" - 53", 4 lights: 54" - 66"). [6] Airflow (CFM) decreases as duct resistance (static pressure) increases. Values at 0.1"–0.3" SP reflect typical installed conditions.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE 062626